VISIBLE EMISSION NOTA	ATIONS			•	
Inspector: Jame N Coarc	174				
Date of Inspection:	T S				
Shift: 4st Shift or 2nd Sh	nift Ti	me: 5:00 pm			
Unit	Visual		Comments		
	Inspection NORMAL or ABNORMAL				i ji Lik
Visible Emission From Shaker	Nor				
Visible Emission From Discharge Conveyor System	Nor			-	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- **Opacity** is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS		-	•	
Inspector:	amoton				
Date of Inspection:	11 1				
Shift: 1 <sup>st</sup> Shift or (2 <sup>nd</sup> )Sh	lift Ti	me: 500AM)			
Unit	Visual		Comments		
	Inspection NORMAL				
	or <u>ABN</u> ORMAL				
Visible Emission From Shaker	Nor			,	
Visible Emission From Discharge Conveyor System	Nor				

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOT	TIONS		_	·
Inspector:	and the same of th		•	
Date of Inspection:	12/2/11			
Shift: (1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	lift Ti	me: @ 17:00		
Unit	Visual Inspection <u>NOR</u> MAL or ABNORMAL		Comments	
Visible Emission From Shaker	NOW	superatural.		
Visible Emission From Discharge Conveyor System	No2	Allegens,		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			•	
Inspector:	There				
Date of Inspection:	12/3/1	)			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	nift Ti	me: @ 6500			
Unit	Visual		Comments		
	Inspection <u>NORMAL</u> or				
	ABNORMAL.				
Visible Emission From Shaker	Nal	4 jauntana			
Visible Emission From Discharge Conveyor System	Non	galacterin			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS	·
Inspector: RCK PA	Lome	
Date of Inspection: 12/3	/11	
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Si	hift Ti 211d	ime: 5:00AM
Unit	Visual	Comments
	Inspection <u>NOR</u> MAL	
	or ABNORMAL	
Visible Emission From Shaker	NOR	Unadistanted production production in the contract of the cont
Visible Emission From Discharge Conveyor System	A \ 2	**************************************
	NOR	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS ,			·
Inspector: Ted C	ompton			
Date of Inspection:	1/1			
Shift: 1 <sup>st</sup> Shift or (2 <sup>nd</sup> Sh	lift 2nd Ti	ime: 500 AM		
Unit	Visual		Comments	
	Inspection <u>NOR</u> MAL			
	or <b>ABN</b> ORMAL			
Visible Emission From Shaker	nor			
Visible Emission From				
Discharge Conveyor System	an			
	NON			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.



#### **VISIBLE EMISSION NOTATIONS**

VIOIDEE EMICOION NO 171				
Inspector: RICK PAL	OM		•	
Date of Inspection:	11			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Shi	ft T	ime:		
20d		ime: 5200AM		
Unit	Visual Inspection		Comments	
	NORMAL			
	Or .			
以 10 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	<u>ABN</u> ORMAL			
Visible Emission From Shaker				
	Nor	, AMAZON CONTROL CONTR		
Visible Emission From				
Discharge Conveyor System		-eromoston-abbrasidellijärillekabbryggivi-syn-		
	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS				•	
Inspector: Nime N G	arcila					
Date of Inspection:	15/11					
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	oift Ti	me: 500 DM				
Unit	Visual		C	omments		
	Inspection NORMAL					: :
Bur Kinggan principal da sa	or <u>ABN</u> ORMAL					
Visible Emission From Shaker	NOR					
Visible Emission From Discharge Conveyor System	Mor					

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

**VISIBLE EMISSION NOTATIONS** Inspector: Date of Inspection: Shift: 1st Shift or 2<sup>nd</sup> Shift Time: 5:00AM Unit Visual Comments Inspection <u>NOR</u>MAL or **ABNORMAL** Visible Emission From Shaker NOR Visible Emission From Discharge Conveyor System NOR

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS		_		•	
Inspector: Jame N Gaec	ιΆ					
Date of Inspection:	19					
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	nift Ti	ime: 5:00 om				
Unit	Visual			Comments		
	Inspection NORMAL or ABNORMAL					
Visible Emission From Shaker	Nor					polesida de la companya de la compan
Visible Emission From Discharge Conveyor System	Non	dragger auto-party comments and an extended requirements are according to the extended requirements and an extended requirements and an extended requirements and an extended requirements are according to the extended requirements and an extended requirements are according to the extended requirements and an extended requirements are according to the extended requirements.				

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- **Opacity** is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector:	ALOMO			
	7 / i			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	olft Ti 2nd	me: 5,00AN		
Unit	Visual		Comments	
	Inspection <u>NOR</u> MAL			
	or ABNORMAL			
Visible Emission From Shaker	NOR	. regissation transcorregistra comments are consistent as a second and a second are consistent as a se		
Visible Emission From				
Discharge Conveyor System	ハロベ	Georgia de la companya del companya de la companya del companya de la companya del la companya de la companya d		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS	
Inspector: Jame N Gae	CIA	
Date of Inspection:		·
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	ift Ti	ime: 5:00 pm
Unit	Visual Inspection <u>NOR</u> WAL or <u>ABN</u> ORMAL	Comments
Visible Emission From Shaker	NOR	
Visible Emission From Discharge Conveyor System	Nor	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector: Reck to	Acomo			
Date of Inspection:				
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	ift Ti	me: 5:00/AM		
Unit	Visual		Comments	
	Inspection			
	NORMAL or		다 가능했다. 한국( ) 등은 기가 되는 것	
	ABNORMAL		ing Aver TAkbyr -	
Visible Emission From Shaker	NOR	- 1 may make the figure that the second control of the second cont		
Visible Emission From				
Discharge Conveyor System	NOR	-yet mayogat ing pinabagan karang ing m		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS		,	
Inspector: Ted (, ~,	pton		_	
Date of Inspection:	' }			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	lift 2nd Ti	me: 500AM		
Unit	Visual Inspection		Comments	
	<u>NOR</u> MAL or ABNORMAL			
Visible Emission From Shaker	Nor			
Visible Emission From Discharge Conveyor System	<b>∅</b>	The state of the s		
Discharge Conveyor System	Nor			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

D.1.12 Daily Visible Emissions Notations Per Each Daylight Shift
(Stack SDS 04)

VISIBLE EMISSION NOTA	TIONS		_	•
Inspector:	empt an		,	
Date of Inspection:	110.			
Shift: 1 <sup>st</sup> Shift or 2 <sup>ftg</sup> Sh	oift Ti	me: 500 AM		
Unit	Visual		Comments	
	Inspection <u>NOR</u> MAL or <u>ABN</u> ORMAL			
Visible Emission From Shaker	0/-			
Visible Emission From Discharge Conveyor System	Nor Nor			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.

  Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the
- background.

•					
VISIBLE EMISSION NOTA	TIONS				
Inspector:	PALOMO	i			
Date of Inspection:	12/12	_   1)			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	A	me: 5100AM			
Unit	Visual		Comments		
	Inspection <u>NOR</u> MAL				1 ;
	or <u>ABN</u> ORMAL			•	
Visible Emission From Shaker	NOR	Commence of the Commence of th			
Visible Emission From	- · · · ·				
Discharge Conveyor System	NOR	Autor region and the impossible color dependence of the facility of the facili			

Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.

Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the

background.

VISIBLE EMISSION NOTA	TIONS			•
Inspector: Ted Con	npt.n	`		
Date of Inspection:			,	
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	ift Ti	me: /700		
Unit	Visual Inspection		Comments	
	<u>NOR</u> MAL or			
Visible Emission From Shaker	ABNORMAL			-
Visible Emission From Discharge Conveyor System	Nor			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS				•	
Inspector: Jame N Care	C/A-					
Date of Inspection:	. ,					
Shift: 1 <sup>st</sup> Shift, or 2 <sup>nd</sup> SI	nift Ti	me: 5:60 pm				
Unit	Visual			Comments		
	Inspection NORMAL or ABNORMAL					
Visible Emission From Shaker	NER	The second secon			The contract of the contract o	
Visible Emission From Discharge Conveyor System	NOR		Physical Physical Printers Page 14 Aug 1979 accus Reposit Andreacours			Manufacture and the second


- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector: Rick PA	LOMO			
Date of Inspection: 12/1	3/11			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	ift 2nd Tir	me: 5800AM		
Unit	Visual		Comments	
	Inspection <u>NOR</u> MAL			
	or <u>ABN</u> ORMAL			
Visible Emission From Shaker	NOR	e <sup>20 TORON</sup> O CONTRACTOR (AND AND AND AND AND AND AND AND AND AND		
Visible Emission From		agina ann neachtalaidh agus na cheann an ann an ann an ann ann ann ann an		
Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			•	
Inspector: RKRA	Lone		•		
1 1	4/11		· · · · · · · · · · · · · · · · · · ·		
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	oift Ti	me: 5800 AM			
Unit	Visual		Comments		
	Inspection <u>NOR</u> MAL or <u>ABN</u> ORMAL				
Visible Emission From Shaker	NOR	***according control control and control a			
Visible Emission From					
Discharge Conveyor System	NOR	The second section of the section of th			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.



VISIBLE EMISSION NOTA	ATIONS		_	
Inspector:	<u> </u>		•	
Date of Inspection:	2/15/11			
Shift: 1 <sup>st</sup> Shift or 2 <sup>na</sup> Sh	nift Ti	me@ 17 00		
Unit	Visual		Comments	•
	Inspection NORMAL		一只有谁人严切答问语 ()	
	or ABNORMAL			
Visible Emission From Shaker	Non	tarifelilitism.		
Visible Emission From Discharge Conveyor System	Nox	garden.		
	l .	l .		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATION	NS				
Inspector: Ted Compt	0 1				
Date of Inspection:	· s				
Shift: 1 <sup>st</sup> Shift or (2 <sup>nd</sup> ) Shift	Ti:	me: 500Am			
Unit	Visual		Comme	nts	
	Inspection <u>NOR</u> MAL				: .:
	or BNORMAL			<i>y</i> -	
Visible Emission From Shaker	Nov	per-sample gas and a good of the first same and the same	·		
Visible Emission From					
Discharge Conveyor System	Var	ASPER SECTION AND APPROXIMATION OF THE CONTRACT OF THE CONTRAC			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

Revised 2/10/09

VISIBLE EMISSION NOTATION	ONS				`•	
Inspector:	ntu~	,				
Date of Inspection: 12/17/11	f.,		<b></b>			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Shift	1001	me: 10+7017 500 AMI				
Unit	Visual			Comments		
	Inspection NORMAL					
	or ABNORMAL	la de la companya de La companya de la co				, i
Visible Emission From Shaker	Vor					
Visible Emission From						
Discharge Conveyor System	Nor	d the contract of the contract				

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			•	
Inspector:	ata				
/ ed Com	f		4		
Date of Inspection:	,				
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	nift Ti	me: 1000 SooAM			
Unit	Visual		Comments		
	Inspection				: :
	<u>NOR</u> MAL				
	or ABNORMAL			•	
Visible Emission From Shaker	Nov				
Visible Emission From					
Discharge Conveyor System	11 -	* Company of the second of the			
	110			 	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBL	E E	MISSI	ON NO	TAT	TONS
--------	-----	-------	-------	-----	------

Inspector: Jahre 4 G	iec X			
Date of Inspection:	' '			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh		me: 8 5:00pm		
Unit	Visual Inspection <u>NOR</u> MAL or <u>ABN</u> ORMAL		Comments	
Visible Emission From Shaker	NOR			Applicate Annual Control of the Cont
Visible Emission From Discharge Conveyor System	Mrn			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			·
Inspector:	Tv .		•	
Date of Inspection:	Klially			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh		me: 0 7 200		
Unit	Visual		Comments	
	Inspection NORMAL or			
	<u>ABN</u> ORMAL			
Visible Emission From Shaker	NOR	pagina Propinsion.		
Visible Emission From Discharge Conveyor System	Non			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- **Opacity** is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.





VISIBLE EMISSION NOTA	ATIONS			•	
Inspector:					
Date of Inspection:	-120/11				
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	ift Ti	me: (7) 00			
<b>Tunit</b>	Visual		Comments		
	Inspection NGRMAL or ABNORMAL				
Visible Emission From Shaker	Na	,,ggg/remin.,			
Visible Emission From Discharge Conveyor System	Nac	villeonisterne			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			•	
Inspector:	1700		]		
Date of Inspection:	12(21/11		,		
Shift: Shift or 2 <sup>nd</sup> Sh	ift Ti	ime: (7:00			
Unit	Visual		Comments		
	Inspection NORMAL or ABNORMAL				
Visible Emission From Shaker	NOR	)-electrons			
Visible Emission From Discharge Conveyor System	Nac	was .			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS				
Inspector: Ted C	ompton				
Date of Inspection:	/11 <sup>1)</sup>				
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh		ime: 500 AM			
Unit	Visual			Comments	 •
	Inspection <u>NOR</u> MAL				 1 1
	or ABNORMAL				
Visible Emission From Shaker	NNS		-		
Visible Emission From	,				
Discharge Conveyor System	Nor				

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			•	
Inspector: Jahn M Cont	EAN				
Date of Inspection:	//				
Shift: 1 <sup>st</sup> Shift or /2 <sup>nd</sup> /Sh	nift Ti	ime: 5:60 pm			
Unit	Visual		Comments		
	Inspection NORMAL or ABNORMAL				
Visible Emission From Shaker	NOR				
Visible Emission From Discharge Conveyor System	Nor			· ·	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			•	
Inspector:	npton				
Date of Inspection:	3//1/		,		
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	lift 200 Ti	me: 500AM			
Unit	Visual		Comments		
	Inspection <u>NOR</u> MAL or		이 기술님이 이 전으로 이 모든 임이 상황에 나가 보았다.		
1000年1月1日 1000年1日 1000	<u>ABN</u> ORMAL				
Visible Emission From Shaker	Nov				
Visible Emission From					
Discharge Conveyor System	2)1/		notition*		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.


VISIBLE EMISSION NOTATION	NS				•	
Inspector: ied Com	ston		•			
Date of Inspection:	r (),					
Shift: 1 <sup>st</sup> Shift or (2 <sup>nd</sup> Shift	Tin	me: 560AM				
Unit	Visual			Comments		
	Inspection					: :
	<u>NOR</u> MAL					•
	or AB <u>N</u> ORMAL			To Arryr -		•
Visible Emission From Shaker		The second secon				
	Var					
Visible Emission From						
Discharge Conveyor System	Vor	:				
]	V 0 1					

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

Revised 2/10/09

VISIBLE EMISSION NOTA	ATIONS				•	
Inspector:	V Coares		_			
Date of Inspection:	1					
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	nift Ti	me: 5:60 pz				
Unit	Visual	<i>*</i>		Comments		
	Inspection <u>NOR</u> MAL or <u>ABN</u> ORMAL					i ji , d
Visible Emission From Shaker	llac					
Visible Emission From Discharge Conveyor System	Norz			Accommons to the second		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.



VISIBLE EMISSION NOTATIONS

Inspector:

Date of Inspection:

Shift: 1<sup>st</sup> Shift or 2<sup>ne</sup> Shift Time:

Shift: 1<sup>st</sup> Shift or 2<sup>ne</sup> Shift Time:

Inspection

NORMAL

or

ABNORMAL

Visible Emission From Shaker

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

Visible Emission From Discharge Conveyor System

VISIBLE EMISSION NOTA	TIONS			•	
Inspector:	GREAGE				
Date of Inspection:	7				
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	ift Ti	me: 5:00 pm			
Unit	Visual		Comments		
	Inspection <u>NOR</u> MAL				
	or <u>ABN</u> ORMAL				
Visible Emission From Shaker	Nor		en de la companya de		
Visible Emission From	,				
Discharge Conveyor System	Nac	graded to confirm a cannot applicable of contaminating and contami	The state of the s		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			•
Inspector:	4			
	6 0 0 1 m		•	
Date of Inspection:	1111			
$\lambda$ $\frac{12/36}{1}$	/ [ / ]		·	
Shift: (1st Shift or 2nd Sh	ift Ti	me:		
		((0)		
Unit	Visual		Comments	
	Inspection			
ingan belandikan periodikan belangan belangan belangan belangan belangan belangan belangan belangan belangan b Bilangan belanggan b	NORMAL			
	or			
	ABNORMAL			
Visible Emission From Shaker	a \	Chief mush hard from the character of th	-	
Violoto Efficación i rom enanci	Nac			
Visible Emission From	, , , , ,			
Discharge Conveyor System	A 1			
2.65a.go cooyor cyotom	Now		·	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.